

View Online at <https://aerobasegroup.com/nsn/5340-01-629-4007>

Mounting Hole Type:

Plain and counterbored

First Leg Length:

Between 4.94 inches and 5.06 inches

Second Leg Length:

Between 2.94 inches and 3.06 inches

End Application:

4910-01-539-6129

Second Leg Width:

Between 2.94 inches and 3.06 inches

First Leg Hole Diameter:

Between 0.44 inches and 0.56 inches

Second Leg Hole Diameter:

Between 0.20 inches and 0.32 inches

Second Leg Distance Between Hole Centers Along Width:

Between 1.94 inches and 2.06 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.44 inches and 0.56 inches

Second Leg Distance From Edge To Hole Center Along Length:

1.50 inches

First Leg Thickness:

Between 0.32 inches and 0.44 inches

Second Leg Thickness:

Between 0.32 inches and 0.44 inches

First Leg Width:

Between 2.94 inches and 3.06 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 1.44 inches and 1.56 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.60 inches and 0.72 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Two holes

Hole Quantity:

3

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Product Name:

Pin angle

Special Features:

Single hole along first leg is counterbored to 1.13 inches diameter .10 inches deep.

Heat Treatment:

T-6 solution heat treated

Material:

Aluminum alloy 6061

Material Specification:

Astm b221 assn standard single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0