## NSN 5340-01-630-5110

Snap-in Threaded Standoff - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5340-01-630-5110

| View Online at https://aerobasegroup.com/nsn/5340-01-630-5110   |
|---|
| Thread Direction:   |
| Right-hand left internal (includes through thread)  |
| Thready Qty Per Inch (tpi):   |
| 56 left internal (includes through thread)  |
| Thread Size:  |
| 0.086 inches left internal (includes through thread)  |
| Left Projection Diameter:   |
| Between 0.207 inches and 0.212 inches   |
| Special Features:   |
| length is .250 inches. Has a rockwell "b" hardness of 70, or a brinell hardness of 125 or less. Base is a hexagon |
| Material:   |
| Stainless steel   |
| Surface Treatment:  |
| Passivate   |
| Surface Treatment Specification:  |
| Astm a380 assn standard single treatment response   |
| Style Designator:   |
| Projection one end left internal thread   |
| Thread Series Designator:   |
| Unc left internal (includes through thread)   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
| <del>-</del>  |
| Demilitarization:   |
| No  |
| Fiig:   |
| A08900  |
|   |