## NSN 5340-01-644-6062

Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-644-6062

Mounting Hole Type:
Plain
First Leg Length:
1.00 inches
Second Leg Length:
1.00 inches
End Application:
5895-01-592-8791
Second Leg Width:
8.33 inches
First Leg Hole Diameter:
Between 0.128 inches and 0.134 inches
First Leg Thickness:
0.125 inches
Second Leg Thickness:
0.125 inches
First Leg Width:
Between 10.08 inches and 10.10 inches
First Leg Distance Between Hole Centers Along Width:
Between 5.99 inches and 6.01 inches
First Leg Distance Between First And Second Hole Centers Along Width:
Between 1.99 inches and 2.01 inches
First Leg Distance Between Second And Third Hole Centers Along Width:
Between 1.99 inches and 2.01 inches
First Leg Distance From Edge To Hole Center Along Width:
Between 1.03 inches and 1.05 inches
First Leg Distance From Edge To Hole Center Along Length:
Between 0.55 inches and 0.57 inches
First Leg Style:
Square
Second Leg Style:
Square
Second Leg Hole Arrangement Style:
No hole
Hole Quantity:
5
Second Leg Relationship To First Leg:
Not identical
Product Name:
Frame, internal, long antenna panel no. 1 & 2

Special Features:

First leg has (5) through mounting holes. Color is seafoam green number 24533 per fed-std-595.

## NSN 5340-01-644-6062

Angle Bracket - Page 2 of 2

Mil-dtl-5541 spec.



Material:
Aluminum alloy 6063
Material Specification:
Astm b221 assn standard single material response
Surface Treatment:
Chromate
Surface Treatment Specification:
$\label{eq:milder} \mbox{Mil-dtl-5541}, \ \mbox{type 1}, \ \mbox{class 3 military specification single treatment response}$
Style Designator:
Angle
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A042a0
Mil-std (military Standard):