

View Online at <https://aerobasegroup.com/nsn/5340-01-644-9397>

Mounting Hole Type:

Countersunk and plain

First Leg Length:

Between 1.27 inches and 1.33 inches

Second Leg Length:

Between 0.67 inches and 0.73 inches

End Application:

5895-01-592-8791

Second Leg Width:

Between 11.24 inches and 11.26 inches

First Leg Thickness:

0.125 inches

Second Leg Thickness:

0.125 inches

Center Section Height:

Between 20.60 inches and 20.66 inches

Center Section Width:

Between 16.24 inches and 16.26 inches

Center Section Thickness:

0.125 inches

First Leg Width:

Between 11.69 inches and 11.71 inches

First Leg Distance Between First And Second Hole Centers Along Width:

2.00 inches

First Leg Distance Between Second And Third Hole Centers Along Width:

3.00 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.84 inches and 0.86 inches

First Leg Distance From Edge To Hole Center Along Length:

0.4 inches

First Leg Style:

Corner radius

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

No hole

Hole Quantity:

19

Second Leg Relationship To First Leg:

Not identical

Product Name:

Plate, top

Special Features:

Bracket has (19) total holes. The first leg has (5) mounting holes, (3) with .375 inch through diameter, and (2) with .500 inch through diameter. Center section has (14) holes, (6) with .350 inch through diameter countersunk to .515 inches at 82 degrees. Remaining (8) holes lack dimensions.

Heat Treatment:

H-32 strain hardened

Material:

Aluminum alloy 5052

Material Specification:

Astm b209 assn standard single material response

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-dtl-5541, type 1, class 3 military specification single treatment response

Style Designator:

Adjacent angles

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-dtl-5541 spec.