

View Online at <https://aerobasegroup.com/nsn/5340-01-644-9397>

**Mounting Hole Type:**

Countersunk and plain

**First Leg Length:**

Between 1.27 inches and 1.33 inches

**Second Leg Length:**

Between 0.67 inches and 0.73 inches

**End Application:**

5895-01-592-8791

**Second Leg Width:**

Between 11.24 inches and 11.26 inches

**First Leg Thickness:**

0.125 inches

**Second Leg Thickness:**

0.125 inches

**Center Section Height:**

Between 20.60 inches and 20.66 inches

**Center Section Width:**

Between 16.24 inches and 16.26 inches

**Center Section Thickness:**

0.125 inches

**First Leg Width:**

Between 11.69 inches and 11.71 inches

**First Leg Distance Between First And Second Hole Centers Along Width:**

2.00 inches

**First Leg Distance Between Second And Third Hole Centers Along Width:**

3.00 inches

**First Leg Distance From Edge To Hole Center Along Width:**

Between 0.84 inches and 0.86 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.4 inches

**First Leg Style:**

Corner radius

**Second Leg Style:**

Corner radius

**Second Leg Hole Arrangement Style:**

No hole

**Hole Quantity:**

19

**Second Leg Relationship To First Leg:**

Not identical

**Product Name:**

Plate, top

**Special Features:**

Bracket has (19) total holes. The first leg has (5) mounting holes, (3) with .375 inch through diameter, and (2) with .500 inch through diameter. Center section has (14) holes, (6) with .350 inch through diameter countersunk to .515 inches at 82 degrees. Remaining (8) holes lack dimensions.

**Heat Treatment:**

H-32 strain hardened

**Material:**

Aluminum alloy 5052

**Material Specification:**

Astm b209 assn standard single material response

**Surface Treatment:**

Chromate

**Surface Treatment Specification:**

Mil-dtl-5541, type 1, class 3 military specification single treatment response

**Style Designator:**

Adjacent angles

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-dtl-5541 spec.