

View Online at <https://aerobasegroup.com/nsn/5340-01-653-6865>

Material Thickness:

10.4 millimeters

Mounting Hole Diameter:

Between 5.4 millimeters and 5.6 millimeters

Mounting Hole Quantity:

4

Body Width:

Between 50.0 millimeters and 52.0 millimeters

End Application:

5895-01-577-3173

Performance Type:

Not rated

Reversible Feature:

Not included

Pin Removability:

Nonremovable

Knuckle Quantity:

2

Pin Center To Body Edge Distance:

28.5 millimeters

Knuckle Type:

Friction

Material And Location:

Steel, corrosion resisting spring

Product Name:

Position control detent hinge

Special Features:

Radial load performance: max static load is 450 n (100 lbf), average ultimate load is 2600 n (575 lbf); axial load performance: max static load is 450 n (100 lbf) and average ultimate load is 1800 n (400 lbf); cycle life rating for stainless steel is up to 5000; operating temperature range is -40c (-40f) to 80c (180f); mounting holes are designed to accomodate m5 (no.10) mounting hardware with a maximum head diameter of 10.1mm (0.40") and a maximum head height of 4mm (0.16"); hinge has an 80 degree door hold position but can be adjusted to 180 degrees

Style Designator:

Butt

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A25100