

View Online at <https://aerobasegroup.com/nsn/5340-01-657-1351>

**First Leg Length:**

1.00 inches

**Second Leg Length:**

2.25 inches

**End Application:**

Kc-46a se

**Second Leg Width:**

1.00 inches

**First Leg Hole Diameter:**

0.220 inches

**First Leg Thickness:**

0.125 inches

**Second Leg Thickness:**

0.125 inches

**Center Section Height:**

0.73 inches

**Center Section Thickness:**

0.125 inches

**First Leg Width:**

1.00 inches

**First Leg Distance Between Hole Centers Along Length:**

1.00 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.50 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.500 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Corner radius

**Second Leg Hole Arrangement Style:**

No hole

**Second Leg Relationship To First Leg:**

Not identical

**Product Name:**

Bracket, double angl

**Material:**

Aluminum alloy 6061

**Material Specification:**

Astm b209 national specification single material response or astm b221 national specification single material response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625, ty iii, cl 1 military standard single treatment response

**Style Designator:**

Double angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-a-8625 spec.