## NSN 5342-00-726-6366

Tubular Fairlead - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5342-00-726-6366 **Overall Width:** 0.603 inches **Overall Length:** 1.190 inches **End Application:** Rifle, spotting, cal. .50, m8c **Mounting Facility Quantity: Mounting Method:** Unthreaded hole **Features Provided:** Counterbored aperature and countersunk Cable Diameter For Which Designed: 0.400 inches **Mounting Facility Diameter:** 0.156 inches **Overall Height:** 0.650 inches **Special Features:** C-bore 0.500 diameter x 0.690 lg; mtg hole 0.445 from square end; second hole transverse to bore 0.094 diameter 0.145 from square end; end opposite square end cut at 14.0 degrees angle top to bottom; c-sink 0.030 x 45 deg; 15-n-89 hard Material: Steel comp 1117 or steel comp 1118 **Material Specification:** Astm a108 assn standard all material responses **Surface Treatment:** Phosphate manganese or phosphate zinc **Surface Treatment Specification:** Mil-std-171 military standard single treatment response Shelf Life: N/a **Unit Of Measure: Demilitarization:** Yes - demil/mli Fiig:

A03100

Mil-std (military Standard):

Mil-std-171 spec.