NSN 5342-01-069-8089

Quick-connect-disconnect Bracket - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5342-01-069-8089

General Description:

Matl, polycarbonate resin, fed. L-p-393, color, white, fed. Standard 595 no. 37875, dim., 0.960 in. Min, 0.965 in. Maximum lg, 0.557 in. Min, 0.567 in. Maximum w, 0.490 in. Min, 0.510 in. Maximum h, hole data, 1 rd0.175 in. Min, 0.185 in. Maximum dia, ctr located 0.205 in. Min, 0.215 in. Max, fromleft edge, drilled through top, 1 sq, 0.215 in. Min, 0.220 in. Maximum ea side, located, 0.215 in. Min, 0.220 in. Max, thru top, from right end, 0.135 in. Min, 0.145 in.Max, from front edge, slot data, 1 located through front edge to rd hole, ctr 0.205in. Min, 0.215 in. Maximum from left end, 0.063 in. W at hole, 0.180 in. W at frontedge, 1 through rh end from front, 0.594 in. Min, 0.599 in. Maximum dp, 0.278 in. Min, 0.287 in. Maximum from top to ctr

N/a	
Unit Of Measure:	

Demilitarization:

Shelf Life:

No