## NSN 5342-01-115-5530

Quick Release Pin Receptacle - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5342-01-115-5530

Body Diameter:
0.375 inches
Mounting Hole Diameter:
Between 0.128 inches and 0.133 inches
Center To Center Distance Between Mounting Holes:
1.000 inches
Body Length:
1.250 inches
Plate Thickness:
0.163 inches
Plate Width:
0.625 inches
Plate Length:
1.000 inches
Material Accommodated Thickness:
0.063 inches
Pin Accommodation Diameter:
Between 0.250 inches and 0.253 inches
Mounting Plate Style:
Oval
Mounting Plate Type:
Stud
Special Features:
Aluminum alloy qq-a-225/9 body and mtg plate, aluminum alloy qq-a-225/8 alloy 6061 temper t6 plunger retaining disc and sleeve, steel
qq-w-470 spring, steel alloy seat, anodize mil-a-8625; 1.250 in. Lg; 0.625 in. W; 1.000 in. Diameter mtg hole c to c; 0.128 in. Dia. Mtg
hole; type 1 mounting plate for use with 0.250 in. Dia. Pin, 0.063 in. Skin thk
Material:
Aluminum alloy 7075
Material Specification:
Qq-a-225/9 federal specification single material response or qq-a-200/11 federal specification single material response
Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-a-8625 military specification single treatment response
Specification Data:
76301-3-975 manufacturers standard
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No

A05400

Fiig:

## NSN 5342-01-115-5530

Quick Release Pin Receptacle - Page 2 of 2



Mil-std (military Standard):

Mil-a-8625 spec.