NSN 5342-01-184-7821



Quick Release Pin Receptacle - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5342-01-184-7821 **Body Diameter:** 0.375 inches **Mounting Hole Diameter:** Between 0.128 inches and 0.133 inches **Center To Center Distance Between Mounting Holes:** 1.000 inches **Body Length:** 1.250 inches **Plate Thickness:** 0.163 inches Plate Width: 0.625 inches Plate Length: 1.000 inches **Material Accommodated Thickness:** 0.130 inches **Pin Accommodation Diameter:** Between 0.250 inches and 0.253 inches **Mounting Plate Style:** Oval **Mounting Plate Type:** Stud **Special Features:** 3cres ams 5643 cond h1025 17-4ph body, cres astm a582 cl 303 or 303se mtg plate, cres astm a582 cl 303 or 303se or steel qq-s-766 300 series plunger and retaining disc, cres qq-w-423 comp 302 or cres ams 5673 17-7ph spring, passivate qq-p-35; mtg plate diamond shape 0.625 in. W by 0.062 in. W by 0.062 in. Thk; 1.000 in. C to c distance between (2) 0.128 in. Diameter mtg holes; 1.281 in. Lg; 1.250 in. H; 0.371 in. Min 0.376 in. Maximum dia; for use in 0.130 in. Skin w/a 0.250 in. Diameter quick release pin Material: Stainless steel **Material Specification:** -ams-5643 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Specification Data:**

N/a **Unit Of Measure:** Demilitarization:

76301-3-975 manufacturers standard

Fiig:

No

Shelf Life: