Quick Release Pin Receptacle - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5342-01-184-7821

Body Diameter:

0.375 inches

Mounting Hole Diameter:

Between 0.128 inches and 0.133 inches

Center To Center Distance Between Mounting Holes:

1.000 inches

Body Length:

1.250 inches

Plate Thickness:

0.163 inches

Plate Width:

0.625 inches

Plate Length:

1.000 inches

Material Accommodated Thickness:

0.130 inches

Pin Accommodation Diameter:

Between 0.250 inches and 0.253 inches

Mounting Plate Style:

Oval

Mounting Plate Type:

Stud

Special Features:

3cres ams 5643 cond h1025 17-4ph body, cres astm a582 cl 303 or 303se mtg plate, cres astm a582 cl 303 or 303se or steel qq-s-766 300 series plunger and retaining disc, cres qq-w-423 comp 302 or cres ams 5673 17-7ph spring, passivate qq-p-35; mtg plate diamond shape 0.625 in. W by 0.062 in. W by 0.062 in. Thk; 1.000 in. C to c distance between (2) 0.128 in. Diameter mtg holes; 1.281 in. Lg; 1.250 in. H; 0.371 in. Min 0.376 in. Maximum dia; for use in 0.130 in. Skin w/a 0.250 in. Diameter quick release pin

Material:

Stainless steel

Material Specification:

-ams-5643 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Specification Data:

76301-3-975 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig: