## NSN 5342-01-612-4676

Tubular Fairlead - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5342-01-612-4676

End Application:
F10887425
Mounting Facility Quantity:
1
Mounting Method:
Unthreaded hole
Cable Diameter For Which Designed:
0.500 inches
Mounting Facility Diameter:
1.000 inches
Overall Height:
0.620 inches
Product Name:
Cam, release mechanism
Special Features:
Matl includes steel 1215, b1112 or b1113; protective treatment/finish iaw para 5.3.3 of mil-std-171; salt spray test at 36 hours; heat
treatment is cyanide or carbonitride case depth 0.003 to 0.006 inch, file hard to rc 58 file min; cutout has 125 microinch finish; refer to
drawing for additional details
Material:
Steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021
or steel comp 1022 or steel comp 1023 or steel comp 1025 or steel comp 1213
Material Specification:
Qq-s-631 or qq-s-634 or qq-s-637 federal specification single material response
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Filig:
A03100