NSN 5355-00-024-5998

Between 0.251 inches and 0.252 inches

Knob - Page 1 of 2

Inside Diameter:

Shank Length:



View Online at https://aerobasegroup.com/nsn/5355-00-024-5998

| • |
|---|
| Between 0.050 inches and 0.055 inches |
| Counterbore Diameter: |
| Between 0.275 inches and 0.280 inches |
| Counterbore Depth: |
| Between 0.060 inches and 0.070 inches |
| Shank Diameter: |
| Between 0.305 inches and 0.310 inches |
| Shank Style: |
| Straight |
| Setscrew Hole Quantity: |
| 2 |
| Distance From Hole Center To Knob/skirt Base: |
| 0.158 inches |
| Overall Depth: |
| Between 0.245 inches and 0.255 inches |
| Gripping Surface Condition: |
| Smooth |
| Shaft Accommodation Style: |
| Counterbored |
| Outside Diameter: |
| Between 0.495 inches and 0.505 inches |
| Attachment Method: |
| Setscrews |
| Overall Thickness: |
| Between 0.245 inches and 0.255 inches |
| Screw Drive Type: |
| Cross recess type 1 |
| Thready Qty Per Inch (tpi): |
| 32 screw hole |
| Thread Size: |
| 0.138 inches screw hole |
| Material: |
| Copper alloy |
| Style Designator: |
| Round |
| Thread Series Designator: |
| Unc screw hole |
| Shelf Life: |
| N/a |
| |

NSN 5355-00-024-5998

Knob - Page 2 of 2



| ı | 1 | n | iŧ | 1 | : N/ | lea | | | _ | |
|---|---|---|----|----------|------|-----|-----|----|---|---|
| ı | u | n | IT | OI | ١V | ıea | เรเ | JI | е | : |

--

Demilitarization:

No

Fiig:

A530m0