

View Online at <https://aerobasegroup.com/nsn/5355-00-036-6739>

**Inside Diameter:**

Between 0.252 inches and 0.254 inches

**Counterbore Diameter:**

0.640 inches

**Counterbore Depth:**

0.320 inches

**Setscrew Hole Quantity:**

2

**Distance From Hole Center To Knob/skirt Base:**

0.484 inches

**Overall Depth:**

0.730 inches

**Width:**

Between 0.890 inches and 0.930 inches

**Gripping Surface Condition:**

Grip aid

**Shaft Accommodation Style:**

Counterbored

**Length:**

Between 1.325 inches and 1.375 inches

**Skirt Style:**

Stepped

**Reference Marking:**

Line

**Attachment Method:**

Setscrews

**Overall Thickness:**

Between 0.880 inches and 1.040 inches

**End Application:**

Spruance class dd (963), an/sqq-89 surface ship asw combat system, ticonderoga class cg (47), seawolf class ssn, air conditioner, 30 hz 1800btu, kidd class ddg, arleigh burke class ddg, virginia class cgn (41)

**Screw Drive Type:**

Hexagon socket

**Thready Qty Per Inch (tpi):**

32 screw hole

**Thread Size:**

0.164 inches screw hole

**Skirt Outside Diameter:**

1.345 inches

**Skirt Design:**

Nondetachable

**Pointer Design:**

Nondetachable

**Color:**

Black

**Style Designator:**

Pointer

**Thread Series Designator:**

Unc screw hole

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A530m0