

View Online at <https://aerobasegroup.com/nsn/5355-00-036-6739>

Inside Diameter:

Between 0.252 inches and 0.254 inches

Counterbore Diameter:

0.640 inches

Counterbore Depth:

0.320 inches

Setscrew Hole Quantity:

2

Distance From Hole Center To Knob/skirt Base:

0.484 inches

Overall Depth:

0.730 inches

Width:

Between 0.890 inches and 0.930 inches

Gripping Surface Condition:

Grip aid

Shaft Accommodation Style:

Counterbored

Length:

Between 1.325 inches and 1.375 inches

Skirt Style:

Stepped

Reference Marking:

Line

Attachment Method:

Setscrews

Overall Thickness:

Between 0.880 inches and 1.040 inches

End Application:

Spruance class dd (963), an/sqq-89 surface ship asw combat system, ticonderoga class cg (47), seawolf class ssn, air conditioner, 30 hz 1800btu, kidd class ddg, arleigh burke class ddg, virginia class cgn (41)

Screw Drive Type:

Hexagon socket

Thready Qty Per Inch (tpi):

32 screw hole

Thread Size:

0.164 inches screw hole

Skirt Outside Diameter:

1.345 inches

Skirt Design:

Nondetachable

Pointer Design:

Nondetachable

Color:

Black

Style Designator:

Pointer

Thread Series Designator:

Unc screw hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A530m0