

View Online at <https://aerobasegroup.com/nsn/5355-00-054-1813>

Inside Diameter:

Between 0.252 inches and 0.254 inches

Counterbore Diameter:

0.515 inches

Counterbore Depth:

0.266 inches

Setscrew Hole Quantity:

2

Distance From Hole Center To Knob/skirt Base:

0.435 inches

Overall Depth:

0.590 inches

Width:

Between 0.690 inches and 0.730 inches

Gripping Surface Condition:

Grip aid

Shaft Accommodation Style:

Counterbored

Length:

1.720 inches

Skirt Style:

Flared

Reference Marking:

Line and slot

Attachment Method:

Setscrews

Overall Thickness:

Between 0.790 inches and 0.840 inches

Material Transparency:

Opaque

Screw Drive Type:

Hexagon socket

Thready Qty Per Inch (tpi):

32 screw hole

Thread Size:

0.164 inches screw hole

Skirt Outside Diameter:

1.520 inches

Skirt Design:

Nondetachable

Pointer Design:

Nondetachable

Surface Treatment (non-core):

Err-070

Style Designator:

Bar with single pointer

Thread Series Designator:

Unc screw hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530m0