

View Online at <https://aerobasegroup.com/nsn/5355-00-057-2796>

**Inside Diameter:**

Between 3.056 inches and 3.061 inches

**Setscrew Hole Quantity:**

2

**Distance From Hole Center To Knob/skirt Base:**

Between 0.308 inches and 0.318 inches

**Gripping Surface Condition:**

Smooth

**Shaft Accommodation Style:**

Round

**Outside Diameter:**

3.778 inches

**Attachment Method:**

Setscrews

**Overall Thickness:**

1.000 inches

**End Application:**

Forrestal class cv, yellowstone class ad-41 generalpurpose electronic test equipment gpete, iwo jima class lph, sturgeon class ss (637), ticonderoga class cg (47) , arleigh burke class ddg, emory s. Land class as

**Material Transparency:**

Opaque

**Screw Drive Type:**

Hexagon socket

**Thready Qty Per Inch (tpi):**

32 screw hole

**Thread Size:**

0.164 inches screw hole

**Special Features:**

Outer rim slotted with 0.063 in. Wide by 0.016 in. Deep axial finger slots spaced 0.125 in. Between adjoining edges; includes two setscrews per ms51021-32; threads per federal std-h28/2

**Color:**

Black

**Style Designator:**

Round

**Thread Series Designator:**

Unc screw hole

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A530m0