

View Online at <https://aerobasegroup.com/nsn/5355-00-059-6532>

**Inside Diameter:**

Between 0.252 inches and 0.254 inches

**Counterbore Diameter:**

0.485 inches

**Counterbore Depth:**

0.188 inches

**Setscrew Hole Quantity:**

2

**Distance From Hole Center To Knob/skirt Base:**

0.369 inches

**Overall Depth:**

0.568 inches

**Gripping Surface Condition:**

Grip aid

**Shaft Accommodation Style:**

Counterbored

**Outside Diameter:**

1.150 inches

**Reference Marking:**

Arrow

**Attachment Method:**

Setscrews

**Overall Thickness:**

Between 1.025 inches and 1.125 inches

**End Application:**

Aircraft black hawk (mh-60k special operations aircraft), helicopter, carrier based asw, sh-60f, helicopter, search and rescue, hh-60h, helicopter, lamps mark iii, sh-60b

**Material Transparency:**

Opaque

**Screw Drive Type:**

Hexagon socket

**Thready Qty Per Inch (tpi):**

40 screw hole

**Thread Size:**

0.112 inches screw hole

**Special Features:**

Tactile form intensity, 0.610 in. Min dia, 0.650 in. Maximum dia, 0.320 in. Min thickness, 0.370 in. Maximum thickness

**Style Designator:**

Round with triangular face

**Thread Series Designator:**

Unc screw hole

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A530m0