

View Online at <https://aerobasegroup.com/nsn/5355-00-070-2100>

Inside Diameter:

Between 0.252 inches and 0.254 inches

Counterbore Diameter:

0.640 inches

Counterbore Depth:

0.320 inches

Setscrew Hole Quantity:

2

Distance From Hole Center To Knob/skirt Base:

0.484 inches

Overall Depth:

0.730 inches

Gripping Surface Condition:

Grip aid

Shaft Accommodation Style:

Counterbored

Outside Diameter:

Between 0.890 inches and 0.930 inches

Skirt Style:

Flared

Reference Marking:

Arrow

Attachment Method:

Setscrews

Overall Thickness:

Between 1.325 inches and 1.425 inches

Screw Drive Type:

Hexagon socket

Thready Qty Per Inch (tpi):

32 screw hole

Thread Size:

0.164 inches screw hole

Skirt Outside Diameter:

1.525 inches

Skirt Design:

Nondetachable

Special Features:

Tactile form -intensity, 0.792 in. Min dia, 0.832 maximum dia, 0.413 in. Min thickneww, 0463 in. Maximum tickness

Style Designator:

Round with triangular face

Thread Series Designator:

Unc screw hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530m0