NSN 5355-00-146-9766

Knob - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5355-00-146-9766 **Inside Diameter:** Between 0.127 inches and 0.131 inches **Shank Length:** 0.046 inches **Shank Diameter:** 0.515 inches **Shank Style:** Straight **Setscrew Hole Quantity: Distance From Hole Center To Knob/skirt Base:** 0.141 inches **Overall Depth:** 0.234 inches **Gripping Surface Condition:** Grip aid **Shaft Accommodation Style:** Round **Outside Diameter:** 0.625 inches Skirt Style: Ring **Attachment Method:** Setscrews **Overall Thickness:** 0.188 inches Thready Qty Per Inch (tpi): 40 screw hole Thread Size: 0.112 inches screw hole **Skirt Outside Diameter:** 0.515 inches **Skirt Design:** Nondetachable **Special Features:** Slot 0.125 in. Wd, 0.016 in. Dp, with second slot centered in first 0.020 in. Wd, 0.015 in. Dp, edges of knobchamfered 0.015 in., 45 deg, perimeterhas fine diamond knurl Color: Black Material: Aluminum alloy 2024

Anodize

Surface Treatment:

NSN 5355-00-146-9766

Knob - Page 2 of 2



| | | a 161 41 | |
|---------|------------|-----------------|---|
| Surtace | I reatment | Specification | • |
| | | | |

Mil-a-8625 type 1 class 2 military specification single treatment response

Style Designator:

Round

Thread Series Designator:

Unc screw hole

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A530m0

Mil-std (military Standard):

Mil-a-8625 spec.