

View Online at <https://aerobasegroup.com/nsn/5355-00-163-7524>

Inside Diameter:

Between 0.252 inches and 0.254 inches

Counterbore Diameter:

0.640 inches

Counterbore Depth:

0.114 inches

Setscrew Hole Quantity:

2

Distance From Hole Center To Knob/skirt Base:

0.260 inches

Overall Depth:

0.520 inches

Width:

Between 0.890 inches and 0.930 inches

Gripping Surface Condition:

Grip aid

Shaft Accommodation Style:

Counterbored

Length:

Between 1.325 inches and 1.375 inches

Reference Marking:

Line

Attachment Method:

Setscrews

Overall Thickness:

Between 0.760 inches and 0.820 inches

End Application:

Nimitz class cvn, virginia class cgn (41), ticonderoga class cg (47), kidd class ddg, sturgeon class ssn (637), seawolf class ssn, communications systems, an/wrr-7, los angeles class ssn (688), spruance class dd (963)

Screw Drive Type:

Hexagon socket

Thready Qty Per Inch (tpi):

32 screw hole

Thread Size:

0.164 inches screw hole

Pointer Design:

Nondetachable

Color:

Black

Style Designator:

Pointer

Thread Series Designator:

Unc screw hole

Specification Data:

96906-ms91528 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530m0