NSN 5355-00-252-9962

Knob - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5355-00-252-9962 **Inside Diameter:** Between 0.252 inches and 0.254 inches **Counterbore Diameter:** 0.685 inches **Counterbore Depth:** 0.320 inches **Setscrew Hole Quantity:** 2 **Distance From Hole Center To Knob/skirt Base:** 0.489 inches **Overall Depth:** 0.740 inches Width: Between 2.542 inches and 2.592 inches **Gripping Surface Condition:** Grip aid **Shaft Accommodation Style:** Counterbored Skirt Style: Stepped **Attachment Method:** Setscrews **Overall Thickness:** Between 1.890 inches and 1.990 inches **Screw Drive Type:** Hexagon socket Thready Qty Per Inch (tpi): 32 screw hole Thread Size: 0.164 inches screw hole **Skirt Outside Diameter:** 1.690 inches **Skirt Design:** Nondetachable **Special Features:** Tactile form-variable range marker or strobe, 1.167 in. Min dia, 1.207 in. Maximum dia **Style Designator:** Round with crank **Thread Series Designator:** Unc screw hole Shelf Life:

N/a

NSN 5355-00-252-9962

Knob - Page 2 of 2



| | 1 | :. | ~ | 84 | | | | |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

--

Demilitarization:

No

Fiig:

A530m0