

View Online at <https://aerobasegroup.com/nsn/5355-00-255-4706>

**Inside Diameter:**

Between 0.252 inches and 0.254 inches

**Setscrew Hole Quantity:**

2

**Distance From Hole Center To Knob/skirt Base:**

0.489 inches

**Overall Depth:**

0.740 inches

**Width:**

Between 2.326 inches and 2.401 inches

**Gripping Surface Condition:**

Grip aid

**Shaft Accommodation Style:**

Flatted one side

**Skirt Style:**

Stepped

**Attachment Method:**

Setscrews

**Inside Width:**

Between 0.222 inches and 0.227 inches

**Overall Thickness:**

Between 1.708 inches and 1.808 inches

**Material Transparency:**

Opaque

**Screw Drive Type:**

Hexagon socket

**Thready Qty Per Inch (tpi):**

32 screw hole

**Thread Size:**

0.164 inches screw hole

**Skirt Outside Diameter:**

1.690 inches

**Skirt Design:**

Nondetachable

**Special Features:**

Shaft accommodation hole counterbored 0.685 in. Min dia, 0.320 in. Min depth

**Color:**

Black, lusterless

**Style Designator:**

Round with crank

**Thread Series Designator:**

Unc screw hole

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A530m0