

View Online at <https://aerobasegroup.com/nsn/5355-00-275-2752>

**Inside Diameter:**

Between 0.251 inches and 0.252 inches

**Counterbore Diameter:**

0.560 inches

**Counterbore Depth:**

0.060 inches

**Setscrew Hole Quantity:**

1

**Distance From Hole Center To Knob/skirt Base:**

0.220 inches

**Overall Depth:**

0.380 inches

**Fluted Foil Quantity:**

7

**Gripping Surface Condition:**

Grip aid

**Shaft Accommodation Style:**

Counterbored

**Outside Diameter:**

0.750 inches

**Skirt Style:**

Flared

**Reference Marking:**

Line and dot

**Attachment Method:**

Setscrews

**Overall Thickness:**

0.440 inches

**Screw Drive Type:**

Hexagon socket

**Thready Qty Per Inch (tpi):**

32 screw hole

**Thread Size:**

0.138 inches screw hole

**Skirt Outside Diameter:**

0.750 inches

**Skirt Design:**

Nondetachable

**Special Features:**

Additional reference marking: ret

**Color:**

Black

**Material:**

Copper alloy and plastic phenolic and steel

**Style Designator:**

Round with fluted foils

**Thread Series Designator:**

Unc screw hole

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A530m0