

View Online at <https://aerobasegroup.com/nsn/5355-00-275-2883>

**Inside Diameter:**

Between 0.127 inches and 0.129 inches

**Setscrew Hole Quantity:**

2

**Distance From Hole Center To Knob/skirt Base:**

0.484 inches

**Overall Depth:**

0.730 inches

**Gripping Surface Condition:**

Grip aid

**Shaft Accommodation Style:**

Flatted one side

**Outside Diameter:**

Between 0.890 inches and 0.930 inches

**Skirt Style:**

Flared

**Reference Marking:**

Arrow

**Attachment Method:**

Setscrews

**Inside Width:**

Between 0.107 inches and 0.112 inches

**Overall Thickness:**

Between 0.980 inches and 1.040 inches

**Material Transparency:**

Opaque

**Screw Drive Type:**

Hexagon socket

**Thready Qty Per Inch (tpi):**

40 screw hole

**Thread Size:**

0.112 inches screw hole

**Skirt Outside Diameter:**

1.525 inches

**Skirt Design:**

Nondetachable

**Special Features:**

Shaft accommodation hole counterbored 0.640 in. Min diameter 0.320 in. Min depth

**Style Designator:**

Round

**Thread Series Designator:**

Unc screw hole

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A530m0