NSN 5355-00-284-6240

Dial Pointer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5355-00-284-6240

Outside Diameter: 0.750 inches Length: 3.250 inches Attachment Method: Center hole Mounting Hole Diameter: Between 0.437 inches and 0.438 inches Distance From Mounting Hole Center To End Of Pointer: 2.875 inches End Application: Fire pumps, main feed pumps, nimitz class cvn, los angeles class ssn (688), I.P. Compressors, forrestal class cv, supply class ace, a ship class lpd-4 amphibious transport docks, iwo jima class lph, sturgeon class ssn (637); trident hull structure; mars class t-afs 1 Material Transparency: Opaque Special Features: Mounting hole flattened to 0.377 in. Min, 0.378 in. Maximum dia Material: Steel Surface Treatment: Cadmium Style Designator: Tear drop	
Length: 3.250 inches Attachment Method: Center hole Mounting Hole Diameter: Between 0.437 inches and 0.438 inches Distance From Mounting Hole Center To End Of Pointer: 2.875 inches End Application: Fire pumps, main feed pumps, nimitz class cvn, los angeles class ssn (688), I.P. Compressors, forrestal class cv, supply class ace, a ship class lpd-4 amphibious transport docks, iwo jima class lph, sturgeon class ssn (637); trident hull structure; mars class t-afs 1 Material Transparency: Opaque Special Features: Mounting hole flattened to 0.377 in. Min, 0.378 in. Maximum dia Material: Steel Surface Treatment: Cadmium Style Designator:	
3.250 inches Attachment Method: Center hole Mounting Hole Diameter: Between 0.437 inches and 0.438 inches Distance From Mounting Hole Center To End Of Pointer: 2.875 inches End Application: Fire pumps, main feed pumps, nimitz class cvn, los angeles class ssn (688), I.P. Compressors, forrestal class cv, supply class ace, a ship class lpd-4 amphibious transport docks, iwo jima class lph, sturgeon class ssn (637); trident hull structure; mars class t-afs 1 Material Transparency: Opaque Special Features: Mounting hole flattened to 0.377 in. Min, 0.378 in. Maximum dia Material: Steel Surface Treatment: Cadmium Style Designator:	
Attachment Method: Center hole Mounting Hole Diameter: Between 0.437 inches and 0.438 inches Distance From Mounting Hole Center To End Of Pointer: 2.875 inches End Application: Fire pumps, main feed pumps, nimitz class cvn, los angeles class ssn (688), l.P. Compressors, forrestal class cv, supply class ace, a ship class lpd-4 amphibious transport docks, iwo jima class lph, sturgeon class ssn (637); trident hull structure; mars class t-afs 1 Material Transparency: Opaque Special Features: Mounting hole flattened to 0.377 in. Min, 0.378 in. Maximum dia Material: Steel Surface Treatment: Cadmium Style Designator:	
Center hole Mounting Hole Diameter: Between 0.437 inches and 0.438 inches Distance From Mounting Hole Center To End Of Pointer: 2.875 inches End Application: Fire pumps, main feed pumps, nimitz class cvn, los angeles class ssn (688), I.P. Compressors, forrestal class cv, supply class aoe, a ship class lpd-4 amphibious transport docks, iwo jima class lph, sturgeon class ssn (637); trident hull structure; mars class t-afs 1 Material Transparency: Opaque Special Features: Mounting hole flattened to 0.377 in. Min, 0.378 in. Maximum dia Material: Steel Surface Treatment: Cadmium Style Designator:	
Mounting Hole Diameter: Between 0.437 inches and 0.438 inches Distance From Mounting Hole Center To End Of Pointer: 2.875 inches End Application: Fire pumps, main feed pumps, nimitz class cvn, los angeles class ssn (688), l.P. Compressors, forrestal class cv, supply class aoe, a ship class lpd-4 amphibious transport docks, iwo jima class lph, sturgeon class ssn (637); trident hull structure; mars class t-afs 1 Material Transparency: Opaque Special Features: Mounting hole flattened to 0.377 in. Min, 0.378 in. Maximum dia Material: Steel Surface Treatment: Cadmium Style Designator:	
Between 0.437 inches and 0.438 inches Distance From Mounting Hole Center To End Of Pointer: 2.875 inches End Application: Fire pumps, main feed pumps, nimitz class cvn, los angeles class ssn (688), I.P. Compressors, forrestal class cv, supply class aoe, a ship class lpd-4 amphibious transport docks, iwo jima class lph, sturgeon class ssn (637); trident hull structure; mars class t-afs 1 Material Transparency: Opaque Special Features: Mounting hole flattened to 0.377 in. Min, 0.378 in. Maximum dia Material: Steel Surface Treatment: Cadmium Style Designator:	
Distance From Mounting Hole Center To End Of Pointer: 2.875 inches End Application: Fire pumps, main feed pumps, nimitz class cvn, los angeles class ssn (688), l.P. Compressors, forrestal class cv, supply class aoe, a ship class lpd-4 amphibious transport docks, iwo jima class lph, sturgeon class ssn (637); trident hull structure; mars class t-afs 1 Material Transparency: Opaque Special Features: Mounting hole flattened to 0.377 in. Min, 0.378 in. Maximum dia Material: Steel Surface Treatment: Cadmium Style Designator:	
2.875 inches End Application: Fire pumps, main feed pumps, nimitz class cvn, los angeles class ssn (688), I.P. Compressors, forrestal class cv, supply class ace, a ship class lpd-4 amphibious transport docks, iwo jima class lph, sturgeon class ssn (637); trident hull structure; mars class t-afs 1 Material Transparency: Opaque Special Features: Mounting hole flattened to 0.377 in. Min, 0.378 in. Maximum dia Material: Steel Surface Treatment: Cadmium Style Designator:	
End Application: Fire pumps, main feed pumps, nimitz class cvn, los angeles class ssn (688), l.P. Compressors, forrestal class cv, supply class ace, a ship class lpd-4 amphibious transport docks, iwo jima class lph, sturgeon class ssn (637); trident hull structure; mars class t-afs 1 Material Transparency: Opaque Special Features: Mounting hole flattened to 0.377 in. Min, 0.378 in. Maximum dia Material: Steel Surface Treatment: Cadmium Style Designator:	
Fire pumps, main feed pumps, nimitz class cvn, los angeles class ssn (688), I.P. Compressors, forrestal class cv, supply class aoe, a ship class lpd-4 amphibious transport docks, iwo jima class lph, sturgeon class ssn (637); trident hull structure; mars class t-afs 1 Material Transparency: Opaque Special Features: Mounting hole flattened to 0.377 in. Min, 0.378 in. Maximum dia Material: Steel Surface Treatment: Cadmium Style Designator:	
ship class lpd-4 amphibious transport docks, iwo jima class lph, sturgeon class ssn (637); trident hull structure; mars class t-afs 1 Material Transparency: Opaque Special Features: Mounting hole flattened to 0.377 in. Min, 0.378 in. Maximum dia Material: Steel Surface Treatment: Cadmium Style Designator:	
Material Transparency: Opaque Special Features: Mounting hole flattened to 0.377 in. Min, 0.378 in. Maximum dia Material: Steel Surface Treatment: Cadmium Style Designator:	ustin
Opaque Special Features: Mounting hole flattened to 0.377 in. Min, 0.378 in. Maximum dia Material: Steel Surface Treatment: Cadmium Style Designator:	
Special Features: Mounting hole flattened to 0.377 in. Min, 0.378 in. Maximum dia Material: Steel Surface Treatment: Cadmium Style Designator:	
Mounting hole flattened to 0.377 in. Min, 0.378 in. Maximum dia Material: Steel Surface Treatment: Cadmium Style Designator:	
Material: Steel Surface Treatment: Cadmium Style Designator:	
Steel Surface Treatment: Cadmium Style Designator:	
Surface Treatment: Cadmium Style Designator:	
Cadmium Style Designator:	
Style Designator:	
Tear drop	
Shelf Life:	
N/a	
Unit Of Measure:	
	
Demilitarization:	
No	
Fiig:	
A530u0	