

View Online at <https://aerobasegroup.com/nsn/5355-00-324-7702>

**Inside Diameter:**

Between 0.252 inches and 0.254 inches

**Counterbore Diameter:**

0.440 inches

**Counterbore Depth:**

0.320 inches

**Setscrew Hole Quantity:**

2

**Distance From Hole Center To Knob/skirt Base:**

0.484 inches

**Overall Depth:**

0.730 inches

**Width:**

Between 0.890 inches and 0.930 inches

**Gripping Surface Condition:**

Grip aid

**Shaft Accommodation Style:**

Counterbored

**Length:**

Between 1.325 inches and 1.365 inches

**Skirt Style:**

Stepped

**Attachment Method:**

Setscrews

**Overall Thickness:**

Between 1.325 inches and 1.425 inches

**Screw Drive Type:**

Hexagon socket

**Thready Qty Per Inch (tpi):**

32 screw hole

**Thread Size:**

0.164 inches screw hole

**Skirt Outside Diameter:**

1.345 inches

**Skirt Design:**

Nondetachable

**Pointer Design:**

Nondetachable

**Special Features:**

Tactile form-range, 0.792 in. Min dia, 0.832 in. Maximum dia, 0.413 in. Min thickness, 0.463 in. Maximum thickness

**Style Designator:**

Pointed with arched bar

**Thread Series Designator:**

Unc screw hole

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A530m0