

View Online at <https://aerobasegroup.com/nsn/5355-00-408-1723>

Inside Diameter:

Between 0.127 inches and 0.129 inches

Counterbore Diameter:

0.485 inches

Counterbore Depth:

0.026 inches

Setscrew Hole Quantity:

2

Distance From Hole Center To Knob/skirt Base:

0.187 inches

Overall Depth:

0.405 inches

Fluted Foil Quantity:

3

Gripping Surface Condition:

Grip aid

Shaft Accommodation Style:

Counterbored

Outside Diameter:

Between 0.690 inches and 0.730 inches

Attachment Method:

Setscrews

Overall Thickness:

Between 0.856 inches and 0.956 inches

Material Transparency:

Opaque

Screw Drive Type:

Hexagon socket

Thready Qty Per Inch (tpi):

40 screw hole

Thread Size:

0.112 inches screw hole

Special Features:

Tactile form-tune, 0.610 in. Min dia, 0.650 in. Maximum dia, 0.320 in. Min thickness, 0.370. In. Maximum thickness; additional color: orange

Color:

Gray, federal standard 595, 36231

Material:

Aluminum alloy and plastic and stainless steel

Style Designator:

Round with fluted foils

Thread Series Designator:

Unc screw hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530m0