

View Online at <https://aerobasegroup.com/nsn/5355-00-472-9597>

Inside Diameter:

Between 0.127 inches and 0.129 inches

Counterbore Diameter:

0.485 inches

Counterbore Depth:

0.026 inches

Setscrew Hole Quantity:

2

Distance From Hole Center To Knob/skirt Base:

0.187 inches

Overall Depth:

0.405 inches

Width:

Between 0.690 inches and 0.730 inches

Gripping Surface Condition:

Grip aid

Shaft Accommodation Style:

Counterbored

Length:

Between 1.020 inches and 1.070 inches

Reference Marking:

Line

Attachment Method:

Setscrews

Overall Thickness:

Between 0.580 inches and 0.640 inches

End Application:

W/s: helicopter, seasprite h-2; engine, f118-ge-100 (b-2 bomber); hx unique; aircraft, stratofortress b-52; an/avr-2 laser detecting set; oliver perry class ffg

Material Transparency:

Opaque

Screw Drive Type:

Hexagon socket

Thready Qty Per Inch (tpi):

40 screw hole

Thread Size:

0.112 inches screw hole

Pointer Design:

Nondetachable

Style Designator:

Pointer

Thread Series Designator:

Unc screw hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530m0