

View Online at <https://aerobasegroup.com/nsn/5355-00-489-1115>

**Inside Diameter:**

Between 0.252 inches and 0.254 inches

**Counterbore Diameter:**

0.660 inches

**Counterbore Depth:**

Between 0.100 inches and 0.120 inches

**Setscrew Hole Quantity:**

1

**Distance From Hole Center To Knob/skirt Base:**

0.250 inches

**Overall Depth:**

Between 0.500 inches and 0.560 inches

**Gripping Surface Condition:**

Smooth

**Shaft Accommodation Style:**

Counterbored

**Outside Diameter:**

Between 1.240 inches and 1.260 inches

**Skirt Style:**

Ring

**Reference Marking:**

Dot and line

**Attachment Method:**

Setscrews

**Overall Thickness:**

Between 0.672 inches and 0.704 inches

**Screw Drive Type:**

Hexagon socket

**Thready Qty Per Inch (tpi):**

32 screw hole

**Thread Size:**

0.164 inches screw hole

**Skirt Outside Diameter:**

Between 1.240 inches and 1.260 inches

**Skirt Design:**

Nondetachable

**Pointer Design:**

Nondetachable

**Special Features:**

Shaft is flatted on one side

**Material:**

Aluminum

**Material Specification:**

Qq-a-596 federal specification single material response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625 military specification single treatment response

**Style Designator:**

Round with single pointed bar face

**Thread Series Designator:**

Unc screw hole

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A530m0

**Mil-std (military Standard):**

Mil-a-8625 spec.