

View Online at <https://aerobasegroup.com/nsn/5355-00-489-1115>

Inside Diameter:

Between 0.252 inches and 0.254 inches

Counterbore Diameter:

0.660 inches

Counterbore Depth:

Between 0.100 inches and 0.120 inches

Setscrew Hole Quantity:

1

Distance From Hole Center To Knob/skirt Base:

0.250 inches

Overall Depth:

Between 0.500 inches and 0.560 inches

Gripping Surface Condition:

Smooth

Shaft Accommodation Style:

Counterbored

Outside Diameter:

Between 1.240 inches and 1.260 inches

Skirt Style:

Ring

Reference Marking:

Dot and line

Attachment Method:

Setscrews

Overall Thickness:

Between 0.672 inches and 0.704 inches

Screw Drive Type:

Hexagon socket

Thready Qty Per Inch (tpi):

32 screw hole

Thread Size:

0.164 inches screw hole

Skirt Outside Diameter:

Between 1.240 inches and 1.260 inches

Skirt Design:

Nondetachable

Pointer Design:

Nondetachable

Special Features:

Shaft is flatted on one side

Material:

Aluminum

Material Specification:

Qq-a-596 federal specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625 military specification single treatment response

Style Designator:

Round with single pointed bar face

Thread Series Designator:

Unc screw hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530m0

Mil-std (military Standard):

Mil-a-8625 spec.