

View Online at <https://aerobasegroup.com/nsn/5355-00-492-4628>

**Inside Diameter:**

Between 0.252 inches and 0.254 inches

**Setscrew Hole Quantity:**

2

**Distance From Hole Center To Knob/skirt Base:**

0.435 inches

**Overall Depth:**

0.590 inches

**Width:**

Between 0.690 inches and 0.730 inches

**Gripping Surface Condition:**

Grip aid

**Shaft Accommodation Style:**

Flatted one side

**Length:**

1.720 inches

**Skirt Style:**

Flared

**Reference Marking:**

Line and arrow

**Attachment Method:**

Setscrews

**Inside Width:**

Between 0.222 inches and 0.227 inches

**Overall Thickness:**

Between 0.790 inches and 0.840 inches

**Material Transparency:**

Opaque

**Screw Drive Type:**

Hexagon socket

**Thready Qty Per Inch (tpi):**

32 screw hole

**Thread Size:**

0.164 inches screw hole

**Skirt Outside Diameter:**

1.520 inches

**Skirt Design:**

Nondetachable

**Pointer Design:**

Nondetachable

**Special Features:**

Shaft accommodation hole counterbore 0.515 in. Min dia, 0.266 in. Min depth

**Style Designator:**

Bar with single pointer

**Thread Series Designator:**

Unc screw hole

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A530m0