NSN 5355-00-521-7235



| Knob - Page 1 of 2 |
|---|
| View Online at https://aerobasegroup.com/nsn/5355-00-521-7235 |
| Inside Diameter: |
| Between 0.250 inches and 0.251 inches |
| Counterbore Diameter: |
| Between 0.435 inches and 0.445 inches |
| Counterbore Depth: |
| Between 0.088 inches and 0.098 inches |
| Setscrew Hole Quantity: |
| 2 |
| Distance From Hole Center To Knob/skirt Base: |
| Between 0.195 inches and 0.205 inches |
| Overall Depth: |
| Between 0.307 inches and 0.317 inches |
| Width: |
| Between 0.557 inches and 0.567 inches |
| Gripping Surface Condition: |
| Grip aid |
| Shaft Accommodation Style: |
| Counterbored |
| Length: |
| 0.750 inches |
| Reference Marking: |
| Arrow |
| Attachment Method: |
| Setscrews |
| Overall Thickness: |
| Between 0.365 inches and 0.390 inches |
| Screw Drive Type: |
| Hexagon socket |
| Thready Qty Per Inch (tpi): |
| 40 screw hole |
| Thread Size: |
| 0.112 inches screw hole |
| Paintan Paring |

Pointer Design:

Nondetachable

Color:

Black

Material:

Aluminum alloy a380.0

Style Designator:

Pointer

Thread Series Designator:

Unc screw hole

NSN 5355-00-521-7235

Knob - Page 2 of 2



| - | | | | | |
|---|----|----|----|---|---|
| • | he | 1+ | 18 | Δ | • |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530m0