NSN 5355-00-526-1663

View Online at https://aerobasegroup.com/nsn/5355-00-526-1663

Knob - Page 1 of 2



Inside Diameter: 0.250 inches **Shank Length:** 0.750 inches **Shank Diameter:** Between 0.563 inches and 0.813 inches **Shank Style:** Straight **Setscrew Hole Quantity: Distance From Hole Center To Knob/skirt Base:** Between 0.293 inches and 0.357 inches **Overall Depth:** Between 0.563 inches and 0.625 inches Width: Between 1.375 inches and 1.625 inches Fluted Foil Quantity: **Gripping Surface Condition:** Grip aid **Shaft Accommodation Style:** Round **Attachment Method:** Setscrews **Overall Thickness:** Between 1.125 inches and 1.375 inches **Screw Drive Type:** Hexagon socket Thready Qty Per Inch (tpi): 32 screw hole **Thread Size:** 0.190 inches screw hole **Special Features:** Threaded bore 0.250-28 unf Material: Aluminum alloy 356.0 Style Designator: Fluted foils **Thread Series Designator:** Unf screw hole **Specification Data:** 80205-nas1553 professional/industrial association standard

NSN 5355-00-526-1663

Knob - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530m0