

View Online at <https://aerobasegroup.com/nsn/5355-00-547-8144>

**Inside Diameter:**

Between 0.252 inches and 0.254 inches

**Counterbore Diameter:**

0.614 inches

**Counterbore Depth:**

0.114 inches

**Setscrew Hole Quantity:**

2

**Distance From Hole Center To Knob/skirt Base:**

0.260 inches

**Overall Depth:**

0.520 inches

**Gripping Surface Condition:**

Grip aid

**Shaft Accommodation Style:**

Counterbored

**Outside Diameter:**

Between 0.890 inches and 0.930 inches

**Attachment Method:**

Setscrews

**Overall Thickness:**

Between 1.106 inches and 1.206 inches

**Material Transparency:**

Opaque

**Screw Drive Type:**

Hexagon socket

**Thready Qty Per Inch (tpi):**

32 screw hole

**Thread Size:**

0.164 inches screw hole

**Special Features:**

Tactile form-tune, 0.792 in. Min dia, 0.832 in. Maximum dia, 0.413 in. Min thickness, 0.463 in. Maximum thickness

**Color:**

Black, lusterless

**Style Designator:**

Round with fluted foils

**Thread Series Designator:**

Unc screw hole

**Specification Data:**

96906-ms91528 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A530m0