

View Online at <https://aerobasegroup.com/nsn/5355-00-556-0145>

Inside Diameter:

Between 0.252 inches and 0.254 inches

Counterbore Diameter:

0.485 inches

Counterbore Depth:

0.188 inches

Setscrew Hole Quantity:

2

Distance From Hole Center To Knob/skirt Base:

0.369 inches

Overall Depth:

0.568 inches

Width:

Between 0.690 inches and 0.730 inches

Gripping Surface Condition:

Grip aid

Shaft Accommodation Style:

Counterbored

Length:

Between 1.020 inches and 1.070 inches

Skirt Style:

Stepped

Attachment Method:

Setscrews

Overall Thickness:

Between 0.752 inches and 0.812 inches

End Application:

Support equipment, b-1 aircraft, fire control system, missile mk 74 (fcs), communications terminal, satellite an/gsc-3 (v)1, airborne mobile dir air sptctl (2id), (02m jul83)(an/uyq-3a), fire control system, mk 92 (fcs) , aircraft,

Material Transparency:

Opaque

Screw Drive Type:

Hexagon socket

Thready Qty Per Inch (tpi):

40 screw hole

Thread Size:

0.112 inches screw hole

Skirt Outside Diameter:

1.000 inches

Skirt Design:

Nondetachable

Pointer Design:

Nondetachable

Color:

Black, lusterless

Style Designator:

Pointer

Thread Series Designator:

Unc screw hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530m0