

View Online at <https://aerobasegroup.com/nsn/5355-00-556-0151>

Inside Diameter:

Between 0.252 inches and 0.254 inches

Counterbore Diameter:

0.485 inches

Counterbore Depth:

0.188 inches

Setscrew Hole Quantity:

2

Distance From Hole Center To Knob/skirt Base:

0.369 inches

Overall Depth:

0.568 inches

Gripping Surface Condition:

Grip aid

Shaft Accommodation Style:

Counterbored

Outside Diameter:

Between 0.690 inches and 0.730 inches

Skirt Style:

Stepped

Attachment Method:

Setscrews

Overall Thickness:

Between 0.752 inches and 0.812 inches

End Application:

An/spn-35b, support equipment, b-1 aircraft, sonaracoustic miscellaneous, close in weapon system (ciws-phalanx), an/sya-4 data display group, airborne mobile dir air spt ctl (2id), (02m jul83)(an/uyq-3a), boilers, 1200 psi, radio transmitter set, an/urt-23 (rts), ground mobile force satellite comm term (an/tsc-93a), ground mobile force satellite comm term (an/tsc-85a)

Material Transparency:

Opaque

Screw Drive Type:

Hexagon socket

Thready Qty Per Inch (tpi):

40 screw hole

Thread Size:

0.112 inches screw hole

Skirt Outside Diameter:

0.680 inches

Skirt Design:

Nondetachable

Color:

Black, lusterless

Style Designator:

Round

Thread Series Designator:

Unc screw hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530m0