

View Online at <https://aerobasegroup.com/nsn/5355-00-556-0151>

**Inside Diameter:**

Between 0.252 inches and 0.254 inches

**Counterbore Diameter:**

0.485 inches

**Counterbore Depth:**

0.188 inches

**Setscrew Hole Quantity:**

2

**Distance From Hole Center To Knob/skirt Base:**

0.369 inches

**Overall Depth:**

0.568 inches

**Gripping Surface Condition:**

Grip aid

**Shaft Accommodation Style:**

Counterbored

**Outside Diameter:**

Between 0.690 inches and 0.730 inches

**Skirt Style:**

Stepped

**Attachment Method:**

Setscrews

**Overall Thickness:**

Between 0.752 inches and 0.812 inches

**End Application:**

An/spn-35b, support equipment, b-1 aircraft, sonaracoustic miscellaneous, close in weapon system (ciws-phalanx), an/sya-4 data display group, airborne mobile dir air spt ctl (2id), (02m jul83)(an/uyq-3a), boilers, 1200 psi, radio transmitter set, an/urt-23 (rts), ground mobile force satellite comm term (an/tsc-93a), ground mobile force satellite comm term (an/tsc-85a)

**Material Transparency:**

Opaque

**Screw Drive Type:**

Hexagon socket

**Thready Qty Per Inch (tpi):**

40 screw hole

**Thread Size:**

0.112 inches screw hole

**Skirt Outside Diameter:**

0.680 inches

**Skirt Design:**

Nondetachable

**Color:**

Black, lusterless

**Style Designator:**

Round

**Thread Series Designator:**

Unc screw hole

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A530m0