

View Online at <https://aerobasegroup.com/nsn/5355-00-559-4153>

**Inside Diameter:**

Between 0.252 inches and 0.254 inches

**Counterbore Diameter:**

0.640 inches

**Counterbore Depth:**

0.114 inches

**Setscrew Hole Quantity:**

2

**Distance From Hole Center To Knob/skirt Base:**

0.260 inches

**Overall Depth:**

0.520 inches

**Gripping Surface Condition:**

Grip aid

**Shaft Accommodation Style:**

Counterbored

**Outside Diameter:**

Between 0.890 inches and 0.930 inches

**Attachment Method:**

Setscrews

**Overall Thickness:**

Between 1.106 inches and 1.206 inches

**Material Transparency:**

Opaque

**Screw Drive Type:**

Hexagon socket

**Thready Qty Per Inch (tpi):**

32 screw hole

**Thread Size:**

0.164 inches screw hole

**Special Features:**

Tactile form-dimmer, 0.792 in. Min dia, 0.832 in. Maximum dia, 0.413 in. Min thickness, 0.463 in. Maximum thickness, knob color is federal standard 595, no.37038, tactile part is federal standard 595, no. 37875

**Color:**

Black, lusterless

**Style Designator:**

Round with bar face

**Thread Series Designator:**

Unc screw hole

**Specification Data:**

96906-ms91528 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A530m0