

View Online at <https://aerobasegroup.com/nsn/5355-00-559-4155>

Inside Diameter:

Between 0.252 inches and 0.254 inches

Counterbore Diameter:

0.640 inches

Counterbore Depth:

0.114 inches

Setscrew Hole Quantity:

2

Distance From Hole Center To Knob/skirt Base:

0.260 inches

Overall Depth:

0.520 inches

Gripping Surface Condition:

Grip aid

Shaft Accommodation Style:

Counterbored

Outside Diameter:

Between 0.890 inches and 0.930 inches

Attachment Method:

Setscrews

Overall Thickness:

Between 1.106 inches and 1.206 inches

Material Transparency:

Opaque

Screw Drive Type:

Hexagon socket

Thready Qty Per Inch (tpi):

32 screw hole

Thread Size:

0.164 inches screw hole

Special Features:

Tactile form-intensity, 0.792 in. Min dia, 0.832 in. Maximum dia, 0.413 in. Min thickness, 0.463 in. Maximum thickness

Color:

Black, lusterless

Style Designator:

Round with triangular face

Thread Series Designator:

Unc screw hole

Specification Data:

96906-ms91528 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530m0