

View Online at <https://aerobasegroup.com/nsn/5355-00-559-4937>

Inside Diameter:

Between 0.252 inches and 0.254 inches

Counterbore Diameter:

Between 0.360 inches and 0.400 inches

Counterbore Depth:

Between 0.140 inches and 0.180 inches

Setscrew Hole Quantity:

2

Distance From Hole Center To Knob/skirt Base:

Between 0.290 inches and 0.330 inches

Overall Depth:

Between 0.480 inches and 0.520 inches

Gripping Surface Condition:

Smooth

Shaft Accommodation Style:

Counterbored

Outside Diameter:

Between 0.980 inches and 1.020 inches

Reference Marking:

Line

Attachment Method:

Setscrews

Overall Thickness:

Between 0.600 inches and 0.640 inches

Screw Drive Type:

Hexagon socket

Thready Qty Per Inch (tpi):

32 screw hole

Thread Size:

0.164 inches screw hole

Pointer Design:

Nondetachable

Special Features:

Flatted shaft hole, 0.222 in. Min 0.224 in. Maximum w

Color:

Gray, federal standard 595, 36231

Style Designator:

Round with single pointed bar face

Thread Series Designator:

Unc screw hole

Specification Data:

96906-ms21384 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530m0