

View Online at <https://aerobasegroup.com/nsn/5355-00-559-4937>

**Inside Diameter:**

Between 0.252 inches and 0.254 inches

**Counterbore Diameter:**

Between 0.360 inches and 0.400 inches

**Counterbore Depth:**

Between 0.140 inches and 0.180 inches

**Setscrew Hole Quantity:**

2

**Distance From Hole Center To Knob/skirt Base:**

Between 0.290 inches and 0.330 inches

**Overall Depth:**

Between 0.480 inches and 0.520 inches

**Gripping Surface Condition:**

Smooth

**Shaft Accommodation Style:**

Counterbored

**Outside Diameter:**

Between 0.980 inches and 1.020 inches

**Reference Marking:**

Line

**Attachment Method:**

Setscrews

**Overall Thickness:**

Between 0.600 inches and 0.640 inches

**Screw Drive Type:**

Hexagon socket

**Thready Qty Per Inch (tpi):**

32 screw hole

**Thread Size:**

0.164 inches screw hole

**Pointer Design:**

Nondetachable

**Special Features:**

Flatted shaft hole, 0.222 in. Min 0.224 in. Maximum w

**Color:**

Gray, federal standard 595, 36231

**Style Designator:**

Round with single pointed bar face

**Thread Series Designator:**

Unc screw hole

**Specification Data:**

96906-ms21384 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A530m0