

View Online at <https://aerobasegroup.com/nsn/5355-00-559-8942>

Inside Diameter:

Between 0.127 inches and 0.129 inches

Counterbore Diameter:

0.485 inches

Counterbore Depth:

0.026 inches

Setscrew Hole Quantity:

2

Distance From Hole Center To Knob/skirt Base:

0.187 inches

Overall Depth:

0.405 inches

Gripping Surface Condition:

Grip aid

Shaft Accommodation Style:

Counterbored

Outside Diameter:

Between 0.690 inches and 0.730 inches

Attachment Method:

Setscrews

Overall Thickness:

Between 0.580 inches and 0.640 inches

End Application:

Helicopter landing system, lamps mk iii, radar set, an/tpn-18, support equipment, b-1 aircraft, fire control system, mk 92 (fcs)sentinel radar system, sonar acoustic miscellaneous, an/spn-35b, fire control system, missile mk 74 (fcs), radar set, lightweight 3d (an/tps-59), radar, series an/sps-4 (v)

Material Transparency:

Opaque

Screw Drive Type:

Hexagon socket

Thready Qty Per Inch (tpi):

40 screw hole

Thread Size:

0.112 inches screw hole

Color:

Black, lusterless

Style Designator:

Round

Thread Series Designator:

Unc screw hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A530m0