

View Online at <https://aerobasegroup.com/nsn/5355-00-559-8942>

**Inside Diameter:**

Between 0.127 inches and 0.129 inches

**Counterbore Diameter:**

0.485 inches

**Counterbore Depth:**

0.026 inches

**Setscrew Hole Quantity:**

2

**Distance From Hole Center To Knob/skirt Base:**

0.187 inches

**Overall Depth:**

0.405 inches

**Gripping Surface Condition:**

Grip aid

**Shaft Accommodation Style:**

Counterbored

**Outside Diameter:**

Between 0.690 inches and 0.730 inches

**Attachment Method:**

Setscrews

**Overall Thickness:**

Between 0.580 inches and 0.640 inches

**End Application:**

Helicopter landing system, lamps mk iii, radar set, an/tpn-18, support equipment, b-1 aircraft, fire control system, mk 92 (fcs)sentinel radar system, sonar acoustic miscellaneous, an/spn-35b, fire control system, missile mk 74 (fcs), radar set, lightweight 3d (an/tps-59), radar, series an/sps-4 (v)

**Material Transparency:**

Opaque

**Screw Drive Type:**

Hexagon socket

**Thready Qty Per Inch (tpi):**

40 screw hole

**Thread Size:**

0.112 inches screw hole

**Color:**

Black, lusterless

**Style Designator:**

Round

**Thread Series Designator:**

Unc screw hole

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A530m0