

View Online at <https://aerobasegroup.com/nsn/5355-00-579-1210>

**Inside Diameter:**

Between 0.252 inches and 0.254 inches

**Counterbore Diameter:**

0.750 inches

**Counterbore Depth:**

0.250 inches

**Setscrew Hole Quantity:**

2

**Distance From Hole Center To Knob/skirt Base:**

0.427 inches

**Overall Depth:**

0.605 inches

**Gripping Surface Condition:**

Grip aid

**Shaft Accommodation Style:**

Counterbored

**Outside Diameter:**

Between 1.240 inches and 1.280 inches

**Skirt Style:**

Flared

**Reference Marking:**

Arrow

**Attachment Method:**

Setscrews

**Overall Thickness:**

Between 0.820 inches and 0.880 inches

**End Application:**

Aircraft, c-2a (reprocured), tactical air opns module (an/tyq (23), helicopter, mh-53e, helicopter, advance attack, ah-1w, an/srn-25(v) navigation radio set, radio transmitter set, an/urt-23 (rts), fire control system, mk 92 (fcs) , support equipment, b-52 aircraft, sonar acoustic miscellaneous, surface minesweeping systems

**Material Transparency:**

Opaque

**Screw Drive Type:**

Hexagon socket

**Thready Qty Per Inch (tpi):**

32 screw hole

**Thread Size:**

0.164 inches screw hole

**Skirt Outside Diameter:**

1.837 inches

**Skirt Design:**

Nondetachable

**Style Designator:**

Round

**Thread Series Designator:**

Unc screw hole

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A530m0