

View Online at <https://aerobasegroup.com/nsn/5355-00-584-4247>

Inside Diameter:

Between 0.252 inches and 0.254 inches

Counterbore Diameter:

0.685 inches

Counterbore Depth:

0.250 inches

Setscrew Hole Quantity:

2

Distance From Hole Center To Knob/skirt Base:

0.427 inches

Overall Depth:

0.605 inches

Width:

Between 1.795 inches and 1.885 inches

Gripping Surface Condition:

Grip aid

Shaft Accommodation Style:

Counterbored

Skirt Style:

Stepped

Attachment Method:

Setscrews

Overall Thickness:

Between 1.300 inches and 1.400 inches

End Application:

Forrestal class cv, nimitz class cvn, sturgeon class ssn (637), communications terminal, satellite an/gsc-3 (v)1, teletype, model28, virginia class cgn (41), ticonderoga class cg (47), los angeles class ssn (688) , sonar acoustic miscellaneous

Material Transparency:

Opaque

Screw Drive Type:

Hexagon socket

Thready Qty Per Inch (tpi):

32 screw hole

Thread Size:

0.164 inches screw hole

Skirt Outside Diameter:

1.185 inches

Skirt Design:

Nondetachable

Color:

Black, lusterless

Material:

Plastic

Style Designator:

Round with crank

Thread Series Designator:

Unc screw hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530m0