

View Online at <https://aerobasegroup.com/nsn/5355-00-584-4247>

**Inside Diameter:**

Between 0.252 inches and 0.254 inches

**Counterbore Diameter:**

0.685 inches

**Counterbore Depth:**

0.250 inches

**Setscrew Hole Quantity:**

2

**Distance From Hole Center To Knob/skirt Base:**

0.427 inches

**Overall Depth:**

0.605 inches

**Width:**

Between 1.795 inches and 1.885 inches

**Gripping Surface Condition:**

Grip aid

**Shaft Accommodation Style:**

Counterbored

**Skirt Style:**

Stepped

**Attachment Method:**

Setscrews

**Overall Thickness:**

Between 1.300 inches and 1.400 inches

**End Application:**

Forrestal class cv, nimitz class cvn, sturgeon class ssn (637), communications terminal, satellite an/gsc-3 (v)1, teletype, model28, virginia class cgn (41), ticonderoga class cg (47), los angeles class ssn (688) , sonar acoustic miscellaneous

**Material Transparency:**

Opaque

**Screw Drive Type:**

Hexagon socket

**Thready Qty Per Inch (tpi):**

32 screw hole

**Thread Size:**

0.164 inches screw hole

**Skirt Outside Diameter:**

1.185 inches

**Skirt Design:**

Nondetachable

**Color:**

Black, lusterless

**Material:**

Plastic

**Style Designator:**

Round with crank

**Thread Series Designator:**

Unc screw hole

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A530m0