

View Online at <https://aerobasegroup.com/nsn/5355-00-584-5884>

Inside Diameter:

Between 0.251 inches and 0.255 inches

Setscrew Hole Quantity:

2

Distance From Hole Center To Knob/skirt Base:

0.250 inches

Overall Depth:

0.562 inches

Width:

1.438 inches

Fluted Foil Quantity:

8

Gripping Surface Condition:

Grip aid

Shaft Accommodation Style:

Round

Skirt Style:

Flared

Reference Marking:

Line

Attachment Method:

Setscrews

Overall Thickness:

0.875 inches

End Application:

Oliver perry class ffg, virginia class cgn (41), ticonderoga class cg (47), tarawa class lha, nimitz class cvn, forrestal class cv, wasp class lhd, spruance class dd (963)

Screw Drive Type:

Hexagon socket

Thready Qty Per Inch (tpi):

32 screw hole

Thread Size:

0.164 inches screw hole

Skirt Outside Diameter:

1.500 inches

Skirt Design:

Nondetachable

Pointer Design:

Nondetachable

Color:

Black

Style Designator:

Fluted foils

Thread Series Designator:

Unc screw hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530m0