

View Online at <https://aerobasegroup.com/nsn/5355-00-584-5884>

**Inside Diameter:**

Between 0.251 inches and 0.255 inches

**Setscrew Hole Quantity:**

2

**Distance From Hole Center To Knob/skirt Base:**

0.250 inches

**Overall Depth:**

0.562 inches

**Width:**

1.438 inches

**Fluted Foil Quantity:**

8

**Gripping Surface Condition:**

Grip aid

**Shaft Accommodation Style:**

Round

**Skirt Style:**

Flared

**Reference Marking:**

Line

**Attachment Method:**

Setscrews

**Overall Thickness:**

0.875 inches

**End Application:**

Oliver perry class ffg, virginia class cgn (41), ticonderoga class cg (47), tarawa class lha, nimitz class cvn, forrestal class cv, wasp class lhd, spruance class dd (963)

**Screw Drive Type:**

Hexagon socket

**Thread Qty Per Inch (tpi):**

32 screw hole

**Thread Size:**

0.164 inches screw hole

**Skirt Outside Diameter:**

1.500 inches

**Skirt Design:**

Nondetachable

**Pointer Design:**

Nondetachable

**Color:**

Black

**Style Designator:**

Fluted foils

**Thread Series Designator:**

Unc screw hole

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A530m0